

## Sagging Applicator

### Introduction:

The instrument is used for sag resistance evaluation to ensure a uniform film thickness by selecting suitable thickness, which is conducive to verticals, corners, holes, circular pieces of painting controlled.

Viscosity, fineness, thickness are major factors in the impact of sagging.



### Technical Specification:

- ◆ High-grade stainless steel
- ◆ 10 different films incremented by 25 $\mu$ m
- ◆ Wet film width 6mm, Spacing 1.5mm

### Standard:

ASTM D4400, D373

### Order Information:

Order No.	Range ( $\mu$ m)
BEVS 1809/1 Sagging Applicator	50-75-100-125-150-175-200-225-250-275
BEVS 1809/2 Sagging Applicator	250-275-300-325-350-375-400-425-450-475
BEVS 1809/3 Sagging Applicator	450-475-500-525-550-575-600-625-650-675
BEVS 1809/4 Sagging Applicator	650-675-700-725-750-775-800-825-850-875
BEVS 1809/5 Sagging Applicator	850-875-900-925-950-975-1000-1025-1050-1075
BEVS 1809/F1 Quadruplex Sagging Applicator	100-200-300-400-500
BEVS 1809/F2 Quadruplex Sagging Applicator	600-700-800-900-1000

Other sizes are available upon request.